



NOT TO BE USED FOR TITLE V APPLICATIONS

PERMIT APPLICATION

FEB 21 2012

APC 20

PLEASE TYPE OR PRINT AND SUBMIT IN DUPLICATE FOR EACH EMISSION SOURCE. ATTACH APPROPRIATE SOURCE DESCRIPTION FORMS.

1. ORGANIZATION'S LEGAL NAME American Tower Corporation - Paw Paw, TN #308881			/// FOR	APC COMPANY--POINT NO. 78-0229-01
2. MAILING ADDRESS (ST/RD/P.O. BOX) PO Box 63604			/// APC	APC LOG/PERMIT NO. 965492
CITY Phoenix	STATE AZ	ZIP CODE 85082	PHONE WITH AREA CODE 602-284-0280	
3. PRINCIPAL TECHNICAL CONTACT Scot Sandefur			PHONE WITH AREA CODE same	
4. SITE ADDRESS (ST/RD/HWY) 4309 Douglas Dam Rd			COUNTY NAME Sevier	
CITY OR DISTANCE TO NEAREST TOWN Kodak		ZIP CODE 37764	PHONE WITH AREA CODE same	
5. EMISSION SOURCE NO. (NUMBER WHICH UNIQUELY IDENTIFIES THIS SOURCE) E1		PERMIT RENEWAL YES () NO (x)		
6. BRIEF DESCRIPTION OF EMISSION SOURCE Emergency Backup Power - Industrial generator set: 131 hp, 80kW, with 500 gallon diesel fuel belly tank				

7. TYPE OF PERMIT REQUESTED				
CONSTRUCTION (x)	STARTING DATE 3/1/2012	COMPLETION DATE 3/30/2012	LAST PERMIT NUMBER	EMISSION SOURCE REFERENCE NUMBER
OPERATING (x)	DATE CONSTRUCTION STARTED 3/1/2012	DATE COMPLETED 3/30/2012	LAST PERMIT NUMBER	EMISSION SOURCE REFERENCE NUMBER
LOCATION TRANSFER ()	TRANSFER DATE		LAST PERMIT NUMBER	EMISSION SOURCE REFERENCE NUMBER
ADDRESS OF LAST LOCATION				

8. DESCRIBE CHANGES THAT HAVE BEEN MADE TO THIS EQUIPMENT OR OPERATION SINCE THE LAST CONSTRUCTION OR OPERATING PERMIT APPLICATION.		
9. SIGNATURE (APPLICATION MUST BE SIGNED BEFORE IT WILL BE PROCESSED) 		DATE 2/14/12
10. SIGNER'S NAME (TYPE OR PRINT) Scot D. Sandefur	TITLE Director, EHS	PHONE WITH AREA CODE 602-284-0280



NOT TO BE USED FOR TITLE V APPLICATIONS

EMISSION POINT DESCRIPTION

APC 22


PLEASE TYPE OR PRINT AND SUBMIT IN DUPLICATE FOR EACH STACK OR EMISSION POINT.
ATTACH TO THE PERMIT APPLICATION.

1. ORGANIZATION NAME American Tower Corporation - Paw Paw, TN - #308881				/// FOR	APC COMPANY POINT NO.	
2. EMISSION SOURCE NO. (FROM APPLICATION) E1		FLOW DIAGRAM POINT NUMBER		/// APC	APC SEQUENCE NO.	
3. LOCATION: 4309 DouglasDam	LATITUDE 36.00434	LONGITUDE 183.6397	UTM VERTICAL 3987652.98		UTM HORIZONTAL 262,076.93	
4. BRIEF EMISSION POINT DESCRIPTION (ATTACH A SKETCH IF APPROPRIATE): Emergency back-up generator - 131 hp, 80kW, and 300 gal diesel belly tank					DISTANCE TO NEAREST PROPERTY LINE (FT) 75'	
COMPLETE LINES 5 AND 6 IF DIFFERENT FROM THAT ON THE PROCESS OR FUEL BURNING SOURCE DESCRIPTION (APC 21)						
5. NORMAL OPERATION: emergency	HOURS/DAY varies	DAYS/WEEK varies	WEEK/YEAR varies		DAYS/YEAR varies	
6. PERCENT ANNUAL THROUGHPUT:	DEC.-FEB. 25%	MARCH-MAY 25%	JUNE-AUG. 25%		SEPT.-NOV. 25%	
7. STACK OR EMISSION POINT DATA:	HEIGHT ABOVE GRADE (FT) 4'	DIAMETER (FT) 3"	TEMPERATURE (°F) 887	% OF TIME OVER 125°F	DIRECTION OF EXIT (UP, DOWN OR HORIZONTAL) UP	
DATA AT EXIT CONDITIONS:	FLOW (ACTUAL FT ³ /MIN.)	VELOCITY (FT/SEC)	MOISTURE (GRAINS/FT ³)		MOISTURE (PERCENT)	
DATA AT STANDARD CONDITIONS:	FLOW (DRY STD. FT ³ /MIN)	VELOCITY (FT/SEC)	MOISTURE (GRAINS/FT ³)		MOISTURE (PERCENT)	
8. AIR CONTAMINANTS	ACTUAL EMISSIONS			EMISSIONS* EST. METHOD	CONTROL DEVICES*	CONTROL EFFICIENCY%
	EMISSIONS (LBS/HR)		CONCENTRATION			
	AVERAGE	MAXIMUM				
PARTICULATES	0.0346		**	0.0346		
SULFUR DIOXIDE	0.5		***	0.13		
CARBON MONOXIDE	0.202		PPM 0.0505			
ORGANIC COMPOUNDS			PPM			
NITROGEN OXIDES	0.807		PPM	0.202		
FLUORIDES						
OTHER(SPECIFY)	0.75			0.19		
OTHER(SPECIFY)						

(OVER)

9. CHECK TYPES OF MONITORING AND RECORDING INSTRUMENTS THAT ARE ATTACHED:OPACITY MONITOR (), SO₂ MONITOR (), NO_x MONITOR (), OTHER (SPECIFY IN COMMENTS) ()

10. COMMENTS

11. SIGNATURE**DATE**

* REFER TO THE BACK OF THE PERMIT APPLICATION FORM FOR ESTIMATION METHOD AND CONTROL DEVICE CODES.

** EXIT GAS PARTICULATE CONCENTRATION UNITS: PROCESS — GRAINS/DRY STANDARD FT³ (70°F); WOOD FIRED BOILERS — GRAINS/DRY STANDARD FT³ (70°F); ALL OTHER BOILERS — LBS/MILLION BTU HEAT INPUT.

*** EXIT GAS SULFUR DIOXIDE CONCENTRATIONS UNITS: PROCESS — PPM BY VOLUME, DRY BASES; BOILERS — LBS/MILLION BTU HEAT INPUT.



NOT TO BE USED FOR TITLE V APPLICATIONS

PROCESS OR FUEL BURNING SOURCE DESCRIPTION

APC21(& 24)

PLEASE TYPE OR PRINT, SUBMIT IN DUPLICATE AND ATTACH TO THE PERMIT APPLICATION.

1. ORGANIZATION NAME American Tower Corporation - Paw Paw, TN #308881		/// FOR	APC COMPANY-POINT NO.
2. EMISSION SOURCE NO. (AS ON PERMIT APPLICATION) E1	SIC CODE	/// APC	APC PERMIT/LOG NO.

3. DESCRIPTION OF PROCESS OR FUEL BURNING UNIT

Emergency back-up power - Industrial diesel generator set; 131 hp, 80kW, 300 gallon diesel belly tank

4. NORMAL OPERATION: →	HOURS/DAY varies	DAYS/WEEK varies	WEEKS/YEAR varies	DAYS/YEAR varies
5. PERCENT ANNUAL THROUGHPUT: →	DEC.-FEB. 25%	MARCH-MAY 25%	JUNE-AUG. 25%	SEPT.-NOV. 25%
6. TYPE OF PERMIT APPLICATION				(CHECK BELOW ONE ONLY)
PROCESS SOURCE: APPLY FOR A SEPARATE PERMIT FOR EACH SOURCE. (CHECK AT RIGHT, AND COMPLETE LINES 7, 8, 13, AND 14).				()
PROCESS SOURCE WITH IN-PROCESS FUEL: PRODUCTS OF COMBUSTION CONTACT MATERIALS HEATED. APPLY FOR A SEPARATE PERMIT FOR EACH SOURCE. (CHECK AT RIGHT, AND COMPLETE LINES 7, 8, AND 10 THROUGH 14)				()
NON-PROCESS FUEL BURNING SOURCE: PRODUCTS OF COMBUSTION DO NOT CONTACT MATERIALS HEATED. COMPLETE THIS FORM FOR EACH BOILER OR FUEL BURNER AND COMPLETE AN EMISSION POINT DESCRIPTION FORM (APC 22) FOR EACH STACK. (CHECK AT RIGHT, AND COMPLETE LINES 9 TO 14)				()
7. TYPE OF OPERATION: CONTINUOUS, ()		BATCH ()	NORMAL BATCH TIME	NORMAL BATCHES/DAY
8. PROCESS MATERIAL INPUTS AND IN-PROCESS SOLID FUELS	DIAGRAM* REFERENCE	INPUT RATES (POUNDS/HOUR) DESIGN ACTUAL		/(/ (FOR APC USE ONLY) / SCC CODE
A.				/
B.				/
C.				/
D.				/
E.				/
F.				/
G.				/
TOTALS				/

* A SIMPLE PROCESS FLOW DIAGRAM MUST BE ATTACHED.

(OVER)

9. BOILER OR BURNER DATA: (COMPLETE LINES 9 TO 14 USING A SEPARATE FORM FOR EACH BOILER)					
BOILER NUMBER	STACK NUMBER**	TYPE OF FIRING***	RATED BOILER HORSEPOWER	RATED INPUT CAPACITY (10 ⁶ BTU/HR)	OTHER BOILER RATING (SPECIFY CAPACITY AND UNITS)
BOILER SERIAL NO.		DATE CONSTRUCTED	DATE OF LAST MODIFICATION (EXPLAIN IN COMMENTS BELOW).		

** BOILERS WITH A COMMON STACK WILL HAVE THE SAME STACK NUMBER.

*** CYCLONE, SPREADER (WITH OR WITHOUT REINJECTION), PULVERIZED (WET OR DRY BOTTOM, WITH OR WITHOUT REINJECTION), OTHER STOKER (SPECIFY TYPE), HAND FIRED, AUTOMATIC, OR OTHER TYPE (DESCRIBE BELOW IN COMMENTS).

10. FUEL DATA: (COMPLETE FOR A PROCESS SOURCE WITH IN-PROCESS FUEL OR A NON-PROCESS FUEL BURNING SOURCE)							
PRIMARY FUEL TYPE (SPECIFY)				STANDBY FUEL TYPE(S) (SPECIFY)			
FUELS USED	ANNUAL USAGE	HOURLY USAGE		% SULFUR	% ASH	BTU VALUE OF FUEL	(FOR APC ONLY) SCC CODE
		DESIGN	AVERAGE				
NATURAL GAS:	10 ⁶ CUFT	CUFT	CUFT	/ / / /	/ / / /	1,000	
#2 FUEL OIL:	10 ³ GAL	GAL	GAL		/ / / /		
#5 FUEL OIL:	10 ³ GAL	GAL	GAL		/ / / /		
#6 FUEL OIL:	10 ³ GAL	GAL	GAL		/ / / /		
COAL:	TONS	LBS	LBS				
WOOD:	TONS	LBS	LBS	/ / / /	/ / / /		
LIQUID PROPANE:	10 ³ GAL	GAL	GAL	/ / / /	/ / / /	85,000	
OTHER (SPECIFY TYPE & UNITS.):							

11. IF WOOD IS USED AS A FUEL, SPECIFY TYPES AND ESTIMATE PERCENT BY WEIGHT OF BARK

12. IF WOOD IS USED WITH OTHER FUELS, SPECIFY PERCENT BY WEIGHT OF WOOD CHARGED TO THE BURNER.

13. COMMENTS

14. SIGNATURE	DATE
	2/14/12

SD080

GENERAC INDUSTRIAL POWER

Industrial Diesel Generator Set
EPA Emissions Certification: Tier III

80 kW Diesel


Standby Power Rating
100 KVA 80 kW 60 Hz

Prime Power Rating
90 KVA 72 kW 60 Hz



features

- GENERATOR SET**
 - PROTOTYPE & TORSIONALLY TESTED
 - UL2200 TESTED
 - PHOSPHATE PAINT SYSTEM
 - WIDE RANGE OF ENCLOSURES AND VIEWS
- ENGINE**
 - EPA TIER COMPLIANT
 - INDUSTRIAL TESTED, GENERAC APPROVED
 - POWERMATCHED OUTPUT
 - INDUSTRIAL GRADE
- ALTERNATOR**
 - TRUTHOROS PITCH
 - LAYER WOUND ROTOR & STATOR
 - GLASS FIBRE MATERIALS
 - DIGITAL 3-PHASE VOLTAGE CONTROL
- CONTROLS**
 - ENCAPSULATED BOARD W/ SEALED WIRING
 - 4-20MA VOLTAGE TO CURRENT SENSORS
 - SURFACE MOUNT TECHNOLOGY
 - ADVANCED DIAGNOSTICS & COMMUNICATIONS
- ENVIRONMENTALLY FRIENDLY**
 - ENSURES INDUSTRIAL STANDARDS
 - ENGINEERED FOR PERFORMANCE
 - IMPROVES LONGEVITY AND RELIABILITY
- ELIMINATES MAINTENANCE HARMONIC**
 - IMPROVES COOLING
 - HEAT TOLERANT DESIGN
 - FAST AND ACCURATE RESPONSE
- EASY, AFFORDABLE REPLACEMENT**
 - MORE RESISTANT 7471 MONITORING
 - PROVIDES VIBRATION RESISTANCE
 - HARDENED RELIABILITY



primary codes and standards



benefits

- PROVIDES A PROVEN UNIT
- ENSURES A QUALITY PRODUCT
- IMPROVES RESISTANCE TO BLURNTS
- PROVIDES A SINGLE SOURCE SOLUTION
- ENVIRONMENTALLY FRIENDLY
- ENSURES INDUSTRIAL STANDARDS
- ENGINEERED FOR PERFORMANCE
- IMPROVES LONGEVITY AND RELIABILITY
- ELIMINATES MAINTENANCE HARMONIC
- IMPROVES COOLING
- HEAT TOLERANT DESIGN
- FAST AND ACCURATE RESPONSE
- EASY, AFFORDABLE REPLACEMENT
- MORE RESISTANT 7471 MONITORING
- PROVIDES VIBRATION RESISTANCE
- HARDENED RELIABILITY

GENERAC INDUSTRIAL POWER

application and engineering data

SD080

ENGINE SPECIFICATIONS

General Make	Johns / FPT
EPA Emissions Compliance	See Emissions Data Sheet
EPA Emissions Reference	4
Cylinder #	4
Type	Diesel
Displacement - L (cu in.)	6.5 (274)
Bore - mm (in.)	105 (4.1)
Stroke - mm (in.)	132 (5.2)
Compression Ratio	17.5:1
Injection Method	Turbocharged
Control System Type	212244
Piston Type	Aluminum
Crankshaft Type	Forged Steel
Engine Block Type	Cast Iron / Wet Sump
Engine Governing	Electronic
Power Factor	7/0.23%
Frequency Regulation (Steady State)	
Lubrication System	Gear
Oil Pump Type	Full Flow
Oil Filter Type	13.6 (3.6) (14.4)
Crankcase Capacity - L (gall/qty)	

Cooling System	Closed
Cooling System Type	belt Driven Centrifugal
Fan Type	2538 (118)
Fan Blade Number	26
Fan Diameter (in.)	1500
Coolant Heater Rating	1.20
Coolant Heater Standard Voltage	
Fuel System	Ultra Low Sulfur Diesel Fuel
Fuel Specifications	ASTM
Fuel Injection Method	Electronic
Fuel Injection Pump Make	Engine Driven Gear
Fuel Pump Type	Mechanical
Injector Type	Direct Injection
Engine Type	1/4 inch Npt
Fuel Supply Line - mm (in.)	1.5/DC
Fuel Return Line - mm (in.)	90 Amp
Engine Electrical System	995 CCA
Supply Voltage	11
Battery Charging Alternator	12 Volt DC
Battery Size (at 0.0C)	Negative
Battery Group	
Battery Voltage	
Ground Polarity	

ALTERNATOR SPECIFICATIONS

Model	370 mm General
Pole	Revolving
Field Type	14
Insulation Class - Stator	<5%
Total Harmonic Distortion	ISO
Regulation Accuracy Factor (RIF)	One Time Load & Speed
Altenator Type	Direct Excite Dc
Bearing	80
Coupling	72
Load Capacity - Standby	Y
Load Capacity - Prime	
Prototype Short Circuit Test	

Voltage Regulator Type	Digital
Number of Sensed Phases	3
Regulation Accuracy (Steady State)	+/-0.25%

CODES AND STANDARDS COMPLIANCE (WHERE APPLICABLE)

- NEMA 110
- ISO 8528-5
- ISO 1708A 5
- ISO 3046
- BS5514
- SAE J1349
- DIN 2271
- IEEE C62.41 TESTING
- NEMA ICS 1

Rating Definitions:

Standby - Applicable for a varying emergency load for the duration of a utility power outage with no overload capability. (Max. load factor - 75%)
Prime - Applicable for supplying power to a varying load in lieu of utility for an unlimited amount of running time. (Max. load factor - 100%)
12 hours

operating data (60Hz)

SD080

POWER RATINGS (kW)

Single-Phase 120/240VAC @ 1.0pf	
Standby	80
Prime	72
Three-Phase 120/240VAC @ 0.9pf	
Standby	80
Prime	72
Three-Phase 120/240VAC @ 1.0pf	
Standby	80
Prime	72
Three-Phase 240/480VAC @ 0.9pf	
Standby	80
Prime	72

STARTING CAPABILITIES (kW)

480VAC		208/240VAC	
Altitude	kW	Altitude	kW
Standard*	80	Standard*	72
Up to 1000'	79	Up to 1000'	71
Up to 2000'	77	Up to 2000'	69
Up to 3000'	75	Up to 3000'	67
Up to 4000'	73	Up to 4000'	65
Up to 5000'	71	Up to 5000'	63
Up to 6000'	69	Up to 6000'	61
Up to 7000'	67	Up to 7000'	59
Up to 8000'	65	Up to 8000'	57
Up to 9000'	63	Up to 9000'	55
Up to 10000'	61	Up to 10000'	53

*All Generac industrial information utilizes Class H materials. Standby alternator provides less than or equal to Class F temperature rise.

Up to 10000' feet then or equal to Class A temperature rise.

Fuel

Fuel Pump & Filter: 30 gph

Total Fuel Pump Flow (Combustion + Return): 13.6 gph

COOLING

Coolant System Capacity - Gal (L)	4.5 (17.0)
Maximum Radiator Backpressure	1.5 H ₂ O Column

COMBUSTION AIR REQUIREMENTS

Intake Flow at Rated Power: 306 cfm (8.67 m³/min)

EXHAUST

Exhaust Outlet Size (Open End)	3.0"
Maximum Backpressure (Post-Silencer)	1.5"

ENGINE

STANDBY		PRIME	
Altitude	rpm	Altitude	rpm
Standard	1800	Standard	1800
Up to 1000'	1790	Up to 1000'	1790
Up to 2000'	1780	Up to 2000'	1780
Up to 3000'	1770	Up to 3000'	1770
Up to 4000'	1760	Up to 4000'	1760
Up to 5000'	1750	Up to 5000'	1750
Up to 6000'	1740	Up to 6000'	1740
Up to 7000'	1730	Up to 7000'	1730
Up to 8000'	1720	Up to 8000'	1720
Up to 9000'	1710	Up to 9000'	1710
Up to 10000'	1700	Up to 10000'	1700

*** Refer to "Emissions Data Sheet" for maximum BHP for EPA and SOA/CAC permitting purposes.

Generac - Operational characteristics consider maximum ambient conditions. Owner/Dealer may apply under all special conditions. Please consult a Generac Power Systems Industrial Dealer for details. All performance ratings in accordance with ISO8543, BS5514, SAEJ1995 and ISO14357 standards.

standard features and options

SD080

GENERATOR SET

- General
- Generator Voltage: 480VAC
- Generator Frequency: 60Hz
- Generator Power Factor: 0.8
- Generator Efficiency: 90%
- Generator Noise: 72 dBA
- Generator Protection: 100% Overload Protection
- Generator Control: Automatic Voltage Regulation
- Generator Maintenance: 100% Oil-Free
- Generator Enclosure: Aluminum Enclosure

ENGINE SYSTEM

- General
- Engine Type: Diesel
- Engine Power: 80 kW
- Engine Speed: 1800 rpm
- Engine Cooling: Water-Cooled
- Engine Lubrication: 100% Oil-Free
- Engine Maintenance: 100% Oil-Free
- Engine Enclosure: Aluminum Enclosure

CONTROL SYSTEM

- General
- Control Type: Digital
- Control Panel: Touchscreen
- Control Language: English
- Control Features: 100% Overload Protection
- Control Maintenance: 100% Oil-Free
- Control Enclosure: Aluminum Enclosure

- Generator Set
- Generator Voltage: 480VAC
- Generator Frequency: 60Hz
- Generator Power Factor: 0.8
- Generator Efficiency: 90%
- Generator Noise: 72 dBA
- Generator Protection: 100% Overload Protection
- Generator Control: Automatic Voltage Regulation
- Generator Maintenance: 100% Oil-Free
- Generator Enclosure: Aluminum Enclosure

ALTERNATOR SYSTEM

- General
- Alternator Type: Synchronous
- Alternator Power: 80 kW
- Alternator Speed: 1800 rpm
- Alternator Cooling: Water-Cooled
- Alternator Lubrication: 100% Oil-Free
- Alternator Maintenance: 100% Oil-Free
- Alternator Enclosure: Aluminum Enclosure



Know what's below.
Call before you dig.

AMERICAN TOWER BACKUP POWER PROJECT

ATC SITE IDENTIFICATION:

SITE NUMBER: 308881

SITE NAME: PAWP/PAW HOLLOW


SITE ADDRESS: 4309 DOUGLAS DAM ROAD

KODAK, TN 37764-1258

CUSTOMER SITE IDENTIFICATION:

SITE NUMBER: 10089968

SITE NAME:





PROJECT TEAM		PROJECT SUMMARY		PROJECT DESCRIPTION	
ARCHITECT: AMERICAN TOWER CORPORATION 1898 LELAND DRIVE SUITE A MARIETTA, GA 30067 TEL: (678) 265-6705 FAX: (678) 265-6781 CONTACT: JAMES JUSTICE A & E MANAGER CUSTOMER OPERATIONS CONTACT: AMERICAN TOWER CORPORATION 1898 LELAND DRIVE SUITE A MARIETTA, GA 30067 TEL: (678) 265-6705 FAX: (678) 265-6781 CONTACT: JAMES JUSTICE A & E MANAGER ZONING AND BUILDING PERMIT: CONTACT AGENT: JEFFREY STEWART 678-265-6738 LANDLORD: AMERICAN TOWER CORPORATION 10 PRESIDENTIAL WAY WOBURN, MA 01801 TEL: (781) 926-4500 FAX: 781-926-4500 GROUND OWNER: J. JOHNSON AND 236 E MAIN ST #123 SEBASTIANVILLE, TN 37862-3531 UTILITIES: POWER COMPANY: KNOXVILLE UTILITY BOARD TEL: (865) 524-2911 TELEPHONE COMPANY: BELLSOUTH TEL:		ATC SITE SUPERVISOR: JIMMY GIVE 24 HOUR NOTICE BEFORE INSTALL JORDAN HILL TEL: (615) 828-9733 GEOGRAPHIC COORDINATES: LATITUDE: 36° 0' 15.65" N LONGITUDE: 83° 38' 22.9" W GROUND ELEVATION: 1146.7 FT. CODE BLOCK: BUILDING CODE: 2006 INTERNATIONAL BUILDING CODE AT&T OPS FOR POWER CUT OVER: ERIC BAKER TEL: (666) 523-0081 EMAIL: JB2540@ATT.NET		THE PROPOSED PROJECT INCLUDES PLACING A SHARED GENERATOR IN AN EXISTING CELLULAR TOWER COMPOUND. PROJECT NOTES 1. THE FACILITY IS UNMANNED. 2. A TECHNICIAN WILL VISIT THE SITE APPROXIMATELY ONCE A MONTH FOR ROUTINE INSPECTION AND MAINTENANCE. 3. THE PROJECT WILL NOT RESULT IN ANY SIGNIFICANT LAND DISTURBANCE OR EFFECT OF STORM WATER DRAINAGE. 4. NO SANITARY SEWER, POTABLE WATER OR TRASH DISPOSAL IS REQUIRED. 5. HANDICAP ACCESS IS NOT REQUIRED.	
PROJECT LOCATION DIRECTIONS					
FROM NASHVILLE: I-40 EAST TO EXIT 407 BEAR LEFT ON SNYDER RD FOR APPROXIMATELY 1.8 MILES AND TURN LEFT ON HARDIN RD. FOR APPROXIMATELY 1 MILE AND THEN RIGHT ON DOUGLAS DAM RD. ACCESS TO SITE IS GRAVEL ROAD DIRECTLY ACROSS FROM ALLYSON DRIVE.					

STRUCTURAL ENGINEERING
 8505 FREEPORT PARKWAY
 IRVING, TN 37063
 (615) 999-9900
 (615) 999-9900 FAX
 www.at&t.com

ATC SITE NUMBER:
 308881
ATC SITE NAME:
 PAWP/PAW HOLLOW
SITE ADDRESS:
 4309 DOUGLAS DAM ROAD
 KODAK, TN 37764-1258

STAMP NUMBER:
 SHEET NO. 1
 DATE DRAWN: 11/1/12
 JOB NO. 449141
SHEET TITLE:
 TITLE SHEET
 VICINITY MAP
 AND GENERAL
 INFORMATION
SHEET NUMBER:
 T-1
REV. #
 0



NOTE:
THE FOUNDATION DESIGNS ARE BASED ON NORMAL SOILS WITH THE DESIGN PARAMETERS
SOIL UNIT WEIGHT 100 LB/CU FT. AND COHESION $C=2000$ PSF.

② H-FRAME LAYOUT
SCALE: NOT TO SCALE

[illegible]




at&t

AT&T COMMUNICATIONS
TELEPHONE COMPANY
TELEVISION
INTERNET
TELECOM


AT&T COMMUNICATIONS
TELEPHONE COMPANY
TELEVISION
INTERNET
TELECOM

AT&T COMMUNICATIONS
TELEPHONE COMPANY
TELEVISION
INTERNET
TELECOM


AT&T COMMUNICATIONS
TELEPHONE COMPANY
TELEVISION
INTERNET
TELECOM




1 GROUND ROD DETAIL



2 VERTICAL POST CONNECTED TO RING



3 GENERATOR GROUND RING DETAIL




4 CONDUIT TRENCH DETAIL



5 H-FRAME ELEVATION

- NOTES:
1. ALL ELECTRICAL SHALL VERIFY THAT GENERATOR IS INSTALLED SO THAT ELECTRICAL BACK FEEDS ARE NOT POSSIBLE.
 2. ELECTRICAL SHALL VERIFY THAT GROUNDING IS INSTALLED SO THAT NO CIRCULATING CURRENTS ARE POSSIBLE BY FOLLOWING DETAIL 3 SO GROUNDING IS CONNECTED TO EXISTING TOWER.
 3. ALL LIGHTING GROUNDING SHALL BE FREE OF KINKS AND SHALL HAVE LONG BENDS MINIMUM 8".
 4. ALL GROUNDING SHOULD BE INSTALLED PER CLIENT NEC.
 5. SECTION 250 SHALL BE USED FOR ALL GROUNDING TO EXISTING TOWER.
 6. 2" FENCE POSTS AND COVERED FROM GENERATOR GROUND RING.



6 COMPOUND GROUNDING

SCALE
NOT TO SCALE

STRUCTURAL ENGINEERING

8505 FREEMAN PARKWAY
IRVING, TX 75063
(972) 999-8900
FAX (972) 999-8900

ATC SITE NAME:
308881

ATC SITE NAME:
PAWPAP HOLLOW

SITE ADDRESS:
4300 DOLGAS DAM ROAD
KODAK, TN 37764-1258

DATE: 01/11/11

DATE: 01/11/11

DATE: 01/11/11

DATE: 01/11/11

COMPOUND GROUNDING

G-1

0

SCALE
NOT TO SCALE

GENERAC 80KW

GENERAL ASSEMBLY AND INSTALLATION SUPPLEMENT

**100 - 400 Amps,
600 VAC HTS**

Automatic Transfer Switches

100 - 400 Amps, 600 VAC

1 of 2



200 Amp HTS NEMA 1

Standard Features

- Single coil design, electrically operated and mechanically held
- Programmable exercise time
- SPD axi contacts
- Mean contacts are silver alloy
- Conformal coating protects the printed circuit board
- UL1008 Listed
- Indicating LED's for switch position, standby operating, fully available

Optional Accessories

- NEMA 12 enclosure (100-400 Amps)
- NEMA 3R enclosure (All)

Description

- The General H10 Series generator controller.
- The H10 Series H10 Transfer Switch is a "Slave of the Air" Smart Switch designed to operate in conjunction with the Generac H100 Series generator controller.
- The H10 Transfer Switch has 2 wire RS485 communication link to the generator controller.
- The utility voltage is monitored by the H10 along with signal between transfer timing, time delay neutral and inphase transfer.
- Switch operation is initiated by the generator controller.
- All wires and voltage endpoints are programmable through Gen Air Communications Software.
- Time delay neutral and inphase monitor are included.

100-400 Amps, 600 VAC

2 of 2

Interconnections

Switches and Indicators

- System Heavy LED
- Switch Position LED's
- Test Switch
- Return to Normal Switch

- Standby Operating LED
- Utility Available LED
- Fast Test Switch
- Safety Disconnect Switch

Parameter	Value
Steady Accept Voltage	85-95%
Steady Accept Frequency	85-95%
Normal Voltage	1 Watt
Normal Frequency	1-1000 Hz
Acceptable Variation of Duty	1-1000 Hz
Line Interruption Delay	1-1000 Hz
Engine Warning Time	1-300 Seconds
Minimum Run Time	5-90 Minutes
Return to Duty Time	1-30 Minutes
Engine Cooldown Time	1-30 Minutes
Signal Before Transfer Time	1-30 Seconds
Transfer Type	Impulse
Time Difference for Impulse Transfer	2-+0 Seconds

Withstand Current - 600 Volt HTS Series

HITS RATED AMPS					
RUSE PROTECTED					
Maximum RMS Symmetrical	200,000	200,000	200,000	200,000	200,000
Fault Current – Amps	200	400	400	500	600
Maximum Fuse Size – Amps	3.1T	3.1T	3.1T	3.1T	3.1T
Fuse Class					
CIRCUIT BREAKER PROTECTED					
Maximum RMS Symmetrical	14,000	25,000	25,000	35,000	35,000
Fault Current – Amps					
Protective Device Continuous Rating (kAIC) – Amps	150	300	300	600	600

• Tested in accordance with the withstand and closing requirements of UL 1008 and CSA Standards.
 • Current ratings are listed @ 480 VAC.


Unit Dimensions

Technical drawing of the unit showing dimensions H, W, D1, D2, M1, M2, and a detail of the top edge with dimensions V, M, and 0.44 x B.

Terminal Lug Wire Ranges


[illegible]

* Not included in HTS with switched neutral. ** Allowable wire range in brackets is for 2 wires per leg.




PART NO.	RATIO	MODEL NO.	#%	VA	OHMS	"A"	"B"	"C"
0F7784A	100:1A	635-100-01-L36	1	1	.31	65	28	30.5
0F7784B	200:1A	635-200-01-L36	1	5	.95	65	28	30.5
0F7784C	300:1A	A-300-01-L36	1	4.5	.06	112	57.1	27.4
0F7784D	400:1A	A-400-01-L36	1	4	.11	112	57.1	27.4
0F7784E	500:1A	A-500-01-L36	1	6.5	.13	112	57.1	27.4
0F7784F	600:1A	A-600-01-L36	1	7.5	.15	112	57.1	27.4
0F7784G	800:1A	MW-800-01-L36	1	10	.20	143.5	89	29.2
0F7784H	1000:1A	MW-1000-01-L36	1	12	.22	143.5	89	29.2
0F7784J	1500:1A	MW-1500-01-L36	1	15	.50	143.5	89	29.2
0F7784K	2000:1A	MW-2000-01-L36	1	12	.67	143.5	89	29.2
0F7784L	3000:1A	MW-3000-01-L36	1	25	1.0	143.5	89	29.2

CURRENT FLOW METER IN ATS



DETAIL DESCRIPTION OR CONSTRUCTION



AMPACITY TABLE: G-GC CABLES *

1/0	205A
3/0	274A
250	352A

* FOR TYPE "G" CABLES, DERATE THE ABOVE AMPACITIES BY 20% UNLESS ONE PHASE CONDUCTOR IS LEFT UNUSED. VALUES ARE APPLICABLE FOR PRODUCT MANUFACTURED BY GENERAL CABLE. ELECTRICIAN SHALL VERIFY AMPACITIES IF CABLES ARE FROM AN ALTERNATE MANUFACTURER.

CONDUCTOR:

EXTRA FLEXIBLE COPPER CONDUCTOR, ACCORDING ATSM B3.

INSULATION:

100% INSULATION LEVEL, OIL, OZONE AND WATER RESISTANT ETHYLENE PROPYLENE RUBBER (EPR) 90°C NORMAL TEMPERATURE OPERATION, 130°C EMERGENCY OVERLOAD CONDITION, 250° SHORT CIRCUIT CONDITION.

PHASE IDENTIFICATION:

NEUTRAL OR SINGLE COLORED COMPOUNDS WITH SURFACE PRINTING COLOR DESIGNATIONS, ACCORDING ICSA 575.301, IDENTIFICATION PHASE BY PRINTED COLORS: BLACK, WHITE AND RED.

GROUND WIRES:

TWO ROPE-LAY FLEXIBLE STRANDED, COPPER CONDUCTORS.

GROUND CHECK:

ONE YELLOW INSULATED, ROPE-LAY FLEXIBLE STRANDED, COPPER CONDUCTOR.

CORE ASSEMBLY:

THREE PHASE CONDUCTORS, TWO BARE GROUND AND ONE GROUND CHECK CONDUCTORS ARE CABLED TOGETHER WITH A LEFT HAND LAY.

REINFORCEMENT:

AN OPEN REINFORCEMENT IS APPLIED OVER THE CORE FOR MECHANICAL STRENGTH.

JACKET:

EXTRA HEAVY OR HEAVY DUTY ELASTOMER JACKET HIGHLY RESISTANT TO CUTTING, TEAR, SUNLIGHT, OZONE AND FLAME. IT HAS AN EXCELLENT RESISTANCE TO HEAT, MOST OILS, WATER, OIL AND MOST CHEMICALS COMMONLY PRESENT AT MINING FIELD OPERATIONS. THE STANDARD JACKET IS BLACK AND MEETS OR EXCEEDS ALL THE REQUIREMENTS OF ICSA 575.301. ALTERNATE JACKET COLORS ARE AVAILABLE AS REQUESTED.

PACKAGING:

NONMETALLIC WOODEN DRUMS.

OPTIONS:

THERMOPLASTIC POLYURETHANE (TPU) JACKET COLORS.

APPLICATION:

PUT-UP LENGTH (300 m).

STANDARDS/TESTING SPECIFICATIONS

G-GC CABLES MEETS OR EXCEEDS THE REQUIREMENTS OF ICSA 575.301 AND ICSA 548.516.

MARKING

G-GC (3-CONDUCTOR CABLES)

INSTALLATION

G-GC CAN BE USED INDOORS AND OUTDOORS LOCATIONS UNDER VERY SECURE ENVIRONMENTAL CONDITIONS SUCH AS THE ONE COMMONLY PRESENT AT MINING PLACES. CONDUCTOR DESIGN AND BAY MATERIALS USED, ALLOWS THE CABLE TO BE INSTALLED DIRECTLY ON ROUGH MINING FIELDS, NOT REQUIRING ANY PREVIOUS PREPARATION.


G-GC CABLE SPECS

SCALE: NOT TO SCALE


G8500 Series American Tower Installation

This note is for Generac H Panel + HTS installations for American Tower.

1. Unpack the monitor, the antenna, and the data / power cable. The data / power cable is black, with DB9 data connectors on two ends, and a separate pig tail with red and black wire emerging from one of the connectors, labeled OMNIMETRIX END. Make sure that all the components are in good condition, looking for shipping damage.
2. Place the antenna on the roof of the genset, and route the antenna cable through the louvers down into the area of the genset control. BE SURE to provide a drip loop lower than the monitor to keep water from running down the antenna cable into the monitor connection. If the roof is aluminum (non-magnetic), simply mount the antenna near the roof line on the steel side walls.
3. Attach the monitor to the top of the genset control enclosure, as shown.
4. Route the power pigtail with the red and black wires through the cable entry on the back of the genset control, by raising the cable entry gate and sliding the cable through.
5. Tighten the gate screws back!
6. Attach the black wire to the ground terminal, labeled 0 on the right hand end of the terminal strip inside the genset control enclosure. Attach the red wire to the Battery+ terminal on the left hand end of the terminal strip. On 12V systems, it will be labeled "15". On 24V systems, it will be labeled "220A".
7. Attach the Antenna Cable to the front of the monitor, thumb tight.
8. Plug on the data cable, labeled "OmniMetrix End" to the front of the monitor. Tighten screws.
9. Plug the data cable end labeled "Generac End" onto the Generac data connector.
10. Turn on the monitor.
11. Confirm that the LEDs light up and blink. If not, check for power on the terminal strip. If, after 5 minutes, the only LED lit is the Power LED, check the antenna mount and cable connection.
12. Allow 15 minutes for the monitor to log into the network, and then call OmniMetrix at the number below to confirm installation.




Antenna



General Wiring Steps:


1. Install Antenna on or near roof.
2. Connect the Red and Black power wires to the Terminal Strip 183
3. Connect DB9 connector to the OMX unit.
4. Make sure it is the end marked OMNIMETRIX END !
5. Connect DB9 connector to the Generac Diagnostic Port
6. Make sure it is the end marked GENERAC END !
7. Turn on Power Switch on the OMX unit.
8. LEDs should begin to flash.
9. If not, check power connections with volt meter.
10. Wait 15 minutes for unit to make online connection.
11. Call OMX at 770-289-8012 to confirm operation.

OmniMetrix LLC		
G8500 - Generac H Panel		
George P Burdall	Rev 1.0 3/29/2011	2011040100




NOTE: POLARIS TAP MUST BE SECURELY WRAPPED WITH COMMERCIAL GRADE NYLON ELECTRICAL TAPE AFTER INSTALLATION IS COMPLETE


NOTE: BONDING JUMPER/ GROUNDING ELECTRODE CONDUCTOR SHALL BE #4 CU FOR 200A, PER NEC TABLE 250.66.



1 MULTI TENANT METER OPTION
SCALE: NOT TO SCALE




NOTE: POLARIS TAP MUST BE SECURELY WRAPPED WITH COMMERCIAL GRADE NYLON ELECTRICAL TAPE AFTER INSTALLATION IS COMPLETE



THE ALTERNATE NEUTRAL CONNECTION DETAIL IS INTENDED TO SHOW NEUTRAL CONNECTIONS ONLY. ALL OTHER (NON-NEUTRAL) CONNECTIONS SHOWN ON THE MULTI TENANT METER DETAIL TO THE LEFT ARE OMITTED FOR CLARITY.

2 ALTERNATE NEUTRAL CONNECTION
FOR MULTI-TENANT METER OPTION
SCALE: NOT TO SCALE



D.C. NOTIFICATIONS
 REF # DESCRIPTION
 BELL TEST _____
 HI-POUT _____
 S/T _____





GENERAL INFORMATION		(SECTION 1 OF 1)	
SERVICE VOLTAGE:	120/240V 1PH 3W	ENCLOSURE TYPE:	38
BUS RATING & TYPE:	800A ALUMINUM	NEUTRAL RATING:	800A
GROUND BAR:	S.D. BOLTED ALUMINUM, A1 OR C1 CABLE		
S.C. RATING:	22K A.I.C. FULLY RATED		
MAIN DEVICE TYPE:	MAIN LUGS ONLY - BOTTOM CABLE ENTRY		
MECHANICAL - (3) #2-500 kcmil (Cu/Al)			
NEUTRAL TERMINALS:	MECHANICAL - (3) #2-500 kcmil (Cu/Al)		
BOOK CATALOG NO.:	MECHANICAL - (3) #2-500 kcmil (Cu/Al)		
TERMINAL:	COMPLETE ENCLOSURE (INCLUDES TRIM)		
SURFACE MOUNTED			
BOX DIMENSIONS:	57 1/4" (1443mm) H X 24" (609.6mm) W X 12.65" (321.4mm) D		
MAIN GUTTER SIZE:	106 1/2" (2705mm) L X 12 1/2" (317.5mm) W		
LEFT-5" (127.0mm) RIGHT-5" (127.0mm)			
FINAL ID NUMBER/LATE:	(1) 800A		
TYPE:	(2) 120/240V 1PH 3W		
COLOR:	WHITE WITH BLACK LETTERS		
U.L.			
SERVICE ENTRANCE LABEL:			
TRIM LOOK-T-HANDLE LOCK ASSEMBLY			
CIRCUIT DIRECTOR PLASTIC SLEEVE WITH CARD			
PAINTED BOX, A1S 61			
PLANT INFORMATION			
U.L. LABEL:	PART NUMBER	QTY	PART NUMBER
U.L. COTTINGS:	7494A06401	1	EDB2200
NEUTRAL:	6593C08401	2	
GROUND BAR, AL/CU:	6572C78003	1	
CHASSIS ASSEMBLY:	6572C25606	1	
LUG ASSEMBLY:	6572C32906	1	
DEAD FRONT COVER:	6572C27004	1	
DEAD FRONT COVER:	6572C27004	1	
COVER PACKAGING:	4177B04602	1	
DEAD FRONT COVER ASSEMBLY:	6574C74602	1	
PACKAGING:	50C5330201	1	

Notes:


Spot _____ Final Inspection _____

DISTRIBUTION PANEL


SCALE: NOT TO SCALE



SECTION A-A



SECTION B-B



DISTRIBUTION PANEL DETAILS

SCALE: NOT TO SCALE

SD080

GENERAC INDUSTRIAL POWER

Industrial Diesel Generator Set
EPA Emissions Certification: Tier III

80 kW Diesel

Standby Power Rating
100 kVA 80 kW 60 Hz
Prime Power Rating
90 kVA 72 kW 60 Hz

features

benefits

Generator Set	
• PROTOTYPE & TORQUEALLY TESTED	► PROVIDES A PROVEN UNIT
• LISTED TESTED	► ENSURES A QUALITY PRODUCT
• REDUCED MAINTENANCE	► IMPROVES RESISTANCE TO ELEMENTS
• WIDE RANGE OF ENCLOSURES AND TOWERS	► PROVIDES A SILENT SOUND SOLUTION
Engine	
• EPA TIER COMPLIANT	► ENVIRONMENTALLY FRIENDLY
• INDUSTRIAL TESTED, GREENBACK APPROVED	► ENSURES INDUSTRIAL STANDARDS
• POWERMANAGED OUTPUT	► BACKUP FOR PERFORMANCE
• INDUSTRIAL GRADE	► IMPROVES LONGEVITY AND RELIABILITY
Alternator	
• TROUBLE-FREE FITCH	► EASY MAINTENANCE AND HANDLING
• LATER BOUND ROTOR & TENSION	► IMPROVES COOLING
• CAST IRON MATERIAL	► HEAT TOLERANT DESIGN
• DIGITAL SERVICE VOLTAGE CONTROL	► PART AND ACCESSORY SUPPORT
Control	
• REGULATED BOARD W/ SEALED WINDINGS	► EASY APPROACHABLE SERVICE
• 4-700V VOLTAGE TO CURRENT SENSORS	► NOISE RESISTANT 24/7 MONITORING
• LOAD/CONTROL TECHNOLOGY	► PROVIDES VIBRATION RESISTANCE
• ADVANCED DIAGNOSTICS & COMMUNICATIONS	► HARDENED RELIABILITY

primary codes and standards



SD080

ENGINE SPECIFICATIONS

General	
Make	Volvo / PPT
EPA Emissions Compliance	Tier III
EPA Emissions Reference	See Emissions Data Sheet
Cylinder #	4
Type	Direct
Displacement - L (cu in)	4.5 (273)
Bore (mm/in)	105 (4.1)
Stroke (mm/in)	135 (5.3)
Compression Ratio	17.5:1
Inlet Air Method	Turbocharged
Cylinder Head Type	2 Valve
Piston Type	Aluminum
Control Type	Common Rail
Engine Block Type	Cast Iron / Wet Sleeve
Engine Exciting Governor	
Excitator	Excitator
Regulating (Steady State)	+/- 0.25%
Lubrication System	
Oil Pump Type	Gear
Oil Filter Type	Full Flow
Crankcase Capacity - L (gal/imp)	13.6 (3.6) (11.4)
Cooling System	
Water Pump Type	Open
Fan Type	Bel Drive Centrifugal
Fan Motor	250W (10)
Fan Diameter (in)	26
Coolant Hose Wt/Lbs	1500
Coolant Hose Wt/Kg	120
Fuel System	
Fuel Type	Ultra Low Sulfur Diesel Fuel
Fuel Specifications	ASTM
Fuel Filtration (microns)	5
Fuel Inject Pump Make	Standalone
Injector Type	Engine Driven Gear
Engine Type	Mechanical
Engine Type (mm/in)	Direct Injection
Engine Type (mm/in)	17.5 x 135 NPK
Engine Electrical System	
System Voltage	12VDC
Battery Charging Alternator	80 Amp
Battery Size (at 0 cc)	995 CCA
Battery Group	31
Battery Voltage	12 Volt DC
Ground Polarity	Negative

ALTERNATOR SPECIFICATIONS

Model	
380 mm Generator	4
Field Type	
Brushless	11
Insulation Class - Stator	F
Total Harmonic Distortion	<5%
Telephone Interference Factor (TIF)	<50
Alternator Type	
Brushless	11
Load Capacity - Standby	80
Load Capacity - Prime	72
Protocol Short Circuit Test	V

CODES AND STANDARDS COMPLIANCE (WHERE APPLICABLE)

NFPA 99	
NFPA 110	
ISO 8528-5	
ISO 1708A.5	
ISO 3046	
BS5514	
BS5519	
BS5527	
BS5531	
BS5532	
BS5533	
BS5534	
BS5535	
BS5536	
BS5537	
BS5538	
BS5539	
BS5540	
BS5541	
BS5542	
BS5543	
BS5544	
BS5545	
BS5546	
BS5547	
BS5548	
BS5549	
BS5550	
BS5551	
BS5552	
BS5553	
BS5554	
BS5555	
BS5556	
BS5557	
BS5558	
BS5559	
BS5560	
BS5561	
BS5562	
BS5563	
BS5564	
BS5565	
BS5566	
BS5567	
BS5568	
BS5569	
BS5570	
BS5571	
BS5572	
BS5573	
BS5574	
BS5575	
BS5576	
BS5577	
BS5578	
BS5579	
BS5580	
BS5581	
BS5582	
BS5583	
BS5584	
BS5585	
BS5586	
BS5587	
BS5588	
BS5589	
BS5590	
BS5591	
BS5592	
BS5593	
BS5594	
BS5595	
BS5596	
BS5597	
BS5598	
BS5599	
BS5600	
BS5601	
BS5602	
BS5603	
BS5604	
BS5605	
BS5606	
BS5607	
BS5608	
BS5609	
BS5610	
BS5611	
BS5612	
BS5613	
BS5614	
BS5615	
BS5616	
BS5617	
BS5618	
BS5619	
BS5620	
BS5621	
BS5622	
BS5623	
BS5624	
BS5625	
BS5626	
BS5627	
BS5628	
BS5629	
BS5630	
BS5631	
BS5632	
BS5633	
BS5634	
BS5635	
BS5636	
BS5637	
BS5638	
BS5639	
BS5640	
BS5641	
BS5642	
BS5643	
BS5644	
BS5645	
BS5646	
BS5647	
BS5648	
BS5649	
BS5650	
BS5651	
BS5652	
BS5653	
BS5654	
BS5655	
BS5656	
BS5657	
BS5658	
BS5659	
BS5660	
BS5661	
BS5662	
BS5663	
BS5664	
BS5665	
BS5666	
BS5667	
BS5668	
BS5669	
BS5670	
BS5671	
BS5672	
BS5673	
BS5674	
BS5675	
BS5676	
BS5677	
BS5678	
BS5679	
BS5680	
BS5681	
BS5682	
BS5683	
BS5684	
BS5685	
BS5686	
BS5687	
BS5688	
BS5689	
BS5690	
BS5691	
BS5692	
BS5693	
BS5694	
BS5695	
BS5696	
BS5697	
BS5698	
BS5699	
BS5700	
BS5701	
BS5702	
BS5703	
BS5704	
BS5705	
BS5706	
BS5707	
BS5708	
BS5709	
BS5710	
BS5711	
BS5712	
BS5713	
BS5714	
BS5715	
BS5716	
BS5717	
BS5718	
BS5719	
BS5720	
BS5721	
BS5722	
BS5723	
BS5724	
BS5725	
BS5726	
BS5727	
BS5728	
BS5729	
BS5730	
BS5731	
BS5732	
BS5733	
BS5734	
BS5735	
BS5736	
BS5737	
BS5738	
BS5739	
BS5740	
BS5741	
BS5742	
BS5743	
BS5744	
BS5745	
BS5746	
BS5747	
BS5748	
BS5749	
BS5750	
BS5751	
BS5752	
BS5753	
BS5754	
BS5755	
BS5756	
BS5757	
BS5758	
BS5759	
BS5760	
BS5761	
BS5762	
BS5763	
BS5764	
BS5765	
BS5766	
BS5767	
BS5768	
BS5769	
BS5770	
BS5771	
BS5772	
BS5773	
BS5774	
BS5775	
BS5776	
BS5777	
BS5778	
BS5779	
BS5780	
BS5781	
BS5782	
BS5783	
BS5784	
BS5785	
BS5786	
BS5787	
BS5788	
BS5789	
BS5790	
BS5791	
BS5792	
BS5793	
BS5794	
BS5795	
BS5796	
BS5797	
BS5798	
BS5799	
BS5800	
BS5801	
BS5802	
BS5803	
BS5804	
BS5805	
BS5806	
BS5807	
BS5808	
BS5809	
BS5810	
BS5811	
BS5812	
BS5813	
BS5814	
BS5815	
BS5816	
BS5817	
BS5818	
BS5819	
BS5820	
BS5821	
BS5822	
BS5823	
BS5824	
BS5825	
BS5826	
BS5827	
BS5828	
BS5829	
BS5830	
BS5831	
BS5832	
BS5833	
BS5834	
BS5835	
BS5836	
BS5837	
BS5838	
BS5839	
BS5840	
BS5841	
BS5842	
BS5843	
BS5844	
BS5845	
BS5846	
BS5847	
BS5848	
BS5849	
BS5850	
BS5851	
BS5852	
BS5853	
BS5854	
BS5855	
BS5856	
BS5857	
BS5858	
BS5859	
BS5860	
BS5861	
BS5862	
BS5863	
BS5864	
BS5865	
BS5866	
BS5867	
BS5868	
BS5869	
BS5870	
BS5871	
BS5872	
BS5873	
BS5874	
BS5875	
BS5876	
BS5877	
BS5878	
BS5879	
BS5880	
BS5881	
BS5882	
BS5883	
BS5884	
BS5885	
BS5886	
BS5887	
BS5888	
BS5889	
BS5890	
BS5891	
BS5892	
BS5893	
BS5894	
BS5895	
BS5896	
BS5897	
BS5898	
BS5899	
BS5900	
BS5901	
BS5902	
BS5903	
BS5904	
BS5905	
BS5906	
BS5907	
BS5908	
BS5909	
BS5910	
BS5911	
BS5912	
BS5913	
BS5914	
BS5915	
BS5916	
BS5917	
BS5918	
BS5919	
BS5920	
BS5921	
BS5922	
BS5923	
BS5924	
BS5925	
BS5926	
BS5927	
BS5928	
BS5929	
BS5930	
BS5931	
BS5932	
BS5933	
BS5934	
BS5935	
BS5936	
BS5937	
BS5938	
BS5939	
BS5940	
BS5941	
BS5942	
BS5943	
BS5944	
BS5945	
BS5946	
BS5947	
BS5948	
BS5949	
BS5950	
BS5951	
BS5952	
BS5953	
BS5954	
BS5955	
BS5956	
BS5957	
BS5958	
BS5959	
BS5960	
BS5961	
BS5962	
BS5963	
BS5964	
BS5965	
BS5966	
BS5967	
BS5968	
BS5969	
BS5970	
BS5971	
BS5972	
BS5973	
BS5974	
BS5975	
BS5976	
BS5977	
BS5978	
BS5979	
BS5980	
BS5981	
BS5982	
BS5983	
BS5984	
BS5985	
BS5986	
BS5987	
BS5988	
BS5989	
BS5990	
BS5991	
BS5992	
BS5993	
BS5994	
BS5995	
BS5996	
BS5997	
BS5998	
BS5999	
BS6000	

Single-Phase 120/240VAC @ 1.0p
Three-Phase 120/208VAC @ 0.9p
Three-Phase 120/240VAC @ 0.8p
Three-Phase 277/480VAC @ 0.8p
Three-Phase 346/600VAC @ 0.8p

largest 1 process less than or equal to $Carr \wedge \text{time_limit}$ and r_{max}

*Refer to "Emissions Data Sheets" for maximum fuel flow for EPA and SCAQMD permitting purposes

[illegible]

bioRxiv preprint doi: <https://doi.org/10.1101/000000>; this version posted November 1, 2014. The copyright holder for this preprint (which was not certified by peer review) is the author/funder, who has granted bioRxiv a license to display the preprint in perpetuity. It is made available under aCC-BY-NC-ND 4.0 International license.

S-7

○ Aluminum Endcap Qpx

338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130

13A UL Power/Universal Battery Charger

Q



Frequency

- Removable E-Strip (Break Glass-Type, Surface Mount)
- Removable E-Strip (Fixed Mount, Surface Mount)

☐ Low Fuel

☐ Oil Pressure Low (When a steady stream of oil is visible, the oil level is OK)

0

[illegible][illegible]

**WANT TO
KNOW THE TRUTH ABOUT THE
NEW YORK TIMES?**

**EVIDENCE SHOWING GROUND FOR INSTALLATION
FUEL TANK MONITORING SYSTEM**

GENERIC POWER SYSTEMS OWNS THE CARRIER OF THE MESSAGE. WHAT IS SUPPLIED TO CARRIERS AND MUST NOT BE USED FOR ANY PURPOSE OTHER THAN FOR WHAT IT IS SUPPLIED UNDER THE CARRIER VENDOR CONTRACT OR GENERIC POWER SYSTEMS.

SD80
DIESEL 4.5L IVECO



**GENEPAC POWER
SYSTEMS**
Waukegan
P.O. BOX 8
WAUKEGAN, ILL. 53187

INSTALLATION DRAWING

**TURBOCHARGED & AFTERCOOLED
SOUND ATTENUATED ENSL., LVL**

W/ 300 GALLON FTB

FILE NAME	0H5302C-B ATC.DWG		SIZE	11
SCALE	N/A	FIRST USE	D4.5L IVECO	
DWG NO.	0H5302C-ATC		REV	




ITEM #	TANK FITTING	FUNCTION
1	3/8" NPT COUPLING	FUEL SUPPLY
2	3/8" NPT COUPLING	FUEL RETURN
3	4" NPT WELD FLANGE	EMERGENCY VENT (OUTER)
4		FUEL LEVEL
5	2" NPT WELD FLANGE	FUEL FILL
6	4" NPT WELD FLANGE	EMERGENCY VENT (INNER)
7	2" NPT WELD FLANGE	VENT
8	3/4" NPT COUPLING	DRAIN
9	Ø22 HOLE	LEAK DETECTOR

TANK P/N	0H480805T03	0H480905T03	0H480005T03
DIM "A"	330 (13)	635 (25)	940 (37)
TOTAL TANK CAPACITY	388 (94)	734 (194)	154 (305)
USABLE TANK CAPACITY	289 (79)	716 (189)	1134 (300)
DRY WEIGHT (EST)	237 (522)	344 (758)	445 (982)

NOTES:
 1) ALL DIMENSIONS ARE:
 LENGTH: mm (inch)
 WEIGHT: kg (lbs)
 CAPACITY: L (gal)

2) UL #42 LISTED



DRAWING CREATED FROM PRO/ENGINEER
 3D FILE. ECO MODIFICATION TO BE
 APPLIED TO SOLID MODEL ONLY.

INSTALLATION DRAWING

GENERAC

B-GROUP, DW TYPE 2 TANKS

TITLE				
ISSUE DATE:	10/02/09	DWG NO	0H4610A	REV
SIZE	CAGE NO	WT-KG	SHEET	1 of 1
B				
SCALE	0.075			

Ref. All Generac Power Systems fuel tank bases supplied from the factory are manufactured and labeled per U.L. 142 and are warranted through Generac Power Systems.

UL registration number: MH18459

U.L. 142 DOUBLE WALL FUEL TANK BASE SPECIFICATION

Fuel tank base construction:

- Be constructed in accordance with Underwriters Laboratories Standard UL-142. Be constructed in accordance with Flammable and Combustible Liquids Code, NFPA 30; The Standard for Installation and use of Stationary Combustible Engine and Gas Turbines, NFPA 37; and The Standard for Emergency and Standby Power Systems, NFPA 110. Include reinforced steel box channel for generator support, with load rating of 5,000 lbs. per gen-set mounting hole location. Full height gussets shall be provided at gen-set mounting holes. Be shipped with a certificate of Structural/Mechanical Integrity, certifying that it has met standards through rigorous testing and has demonstrated specified capabilities.

Sub Base Tank Testing:

Primary tank and secondary containment basin sections shall be pressurized at 3-5 psi and leak-checked to ensure integrity of sub base weld seams per U.L.-142 standards

Sub Base Tank Fittings:

The sub base tank shall include the following fittings:

- Appropriately sized NPT
- Fuel supply Fuel return fitting
- NPT for normal vent, sized as appropriate NPT for emergency vent, sized as appropriate
- 2" NPT for manual fill
- NPT for level gauge, sized as appropriate.
- 2" NPT for electronic fuel level; includes Low fuel alarm. High fuel level alarm
- NPT fitting for leak detection alarm

Fuel Level Gauge

The sub base tank shall include a direct-reading fuel level gauge.

Low Fuel Level

Factory Pre-set at 40% remaining for Alarm

Factory Pre-set at 20% remaining for Shut-down

High Fuel Level

Factory Pre-set at 90% full for Alarm

Fuel Containment Basin

Sub base tank shall include a welded steel containment basin, sized at a minimum of 110% of the tank capacity to prevent escape of fuel into the environment in the event of a tank rupture. A fuel containment basin leak detector switch shall be provided.

Sub Base Tank Venting

Normal and Emergency Venting:

Normal and Emergency venting shall be sized per U.L. 142 specifications for wetted surface area of tank.

Soil Classification Chart

Ground anchors are designed for different soil classifications: longer models for loose soils, shorter models for harder soils. Prior to installing any ground anchor model, the soil must be tested (with a Soil Test Probe) in order to match approved ground anchor model with the soil class.

WARNING: Before ground anchor installation, determine that the anchor locations around home will not be close to any underground electrical cables, water lines or sewer piping. Failure to determine the location of electrical cables may result in serious personal injury.

Soil Test Probe

The Soil Test Probe is used to determine the soil conditions below the surface near the anchor's helix. Using the Soil Test Probe will ensure maximum anchor holding strength by indicating the proper anchor model for each soil condition. Using the chart provided, a probe reading can be converted to the recommended anchor for every soil condition.

Instructions

- Place probe tip into ground where you intend to place the anchor. Using a 15/16" hex socket with a ratchet or breaker bar, rotate the probe in a clockwise direction. (An electric drive machine with an adaptor head may also be used).
- Drive (rotate) the torque probe into the soil until reaching a depth equal to the length of the anchor being installed.
- To determine the soil classification:
 - Place wrench adaptor onto torque wrench.
 - Insert hex portion of wrench adaptor onto the earth probe.
 - Support probe shaft with one hand, while rotating probe steadily with the wrench. (Do not exceed 600 in. lbs.)
 - Read the torque wrench while rotating probe clockwise.
- Use the soil classification chart to cross reference probe readings. Color codes match those printed on Tie Down's torque probe. If probe reading does not match the anchor for that depth, rotate probe to next anchor depth and check reading. Continue until reading on probe matches anchor length for depth of reading.
- To remove probe, use wrench or electric drive machine in reverse (counter clockwise).

Soil Class	Test Value (in. lbs.)	Soil Description
1	N/A	Sound hard rock.
2	550 +	Very dense sand/or cemented sands, coarse gravel, cobble, preloaded silts, clays and coral.
3	350 to 550	Medium dense coarse sands sandy gravel, very stiff silts and clays.
4a	275 to 350	Loose to medium dense sands, firm to stiff clays and silts, alluvial fill.
4b	175* to 275	Loose sands, firm clays and silts, alluvial fill.

* Below 175 in. lbs., a professional engineer should be consulted

NOTE: Each State, County or Municipality may require a specific anchor from the groups shown for each soil classification. Check local and State regulations first.

TIE DOWN ENGINEERING • 5901 Wheaton Drive • Atlanta GA, 30336
www.tiedown.com • (404) 344-0000 • FAX (404) 349-0401

(IF APPLICABLE)

NOTE
THE INFORMATION AS SHOWN IN THIS
DRAWING WAS PROVIDED BY TIE DOWN
ENGINEERING.